

# Utility sink VK44inset

**Art. no.** VK44NF  
**GTIN** 7393069022032



<b>Overall dimension in mm</b>	485 x 385 x 190
<b>Depth in mm</b>	190
<b>Bowl dim. in mm</b>	440 x 340 x 190
<b>Cut-out dimension, inset model</b>	460 x 360, R85
<b>Waste hole dim. in mm</b>	52
<b>Volume in L</b>	22
<b>Material</b>	AISI 304
<b>Material thickness in mm</b>	0,8
<b>Gross weight in kg</b>	2.50
<b>Pcs per pallet</b>	34

## Description

Utility sink in stainless steel, for inset. Supplied with fixing clips and hole for overflow.

## Installation

Create a hole in the table top using the enclosed 1:1 template. Place the sink in the hole. Fasten the sink to the table top from underneath with the fixing clips.

# Installation VK44inset

## ASSEMBLY:

Included in the box:

- \* Wash basin
- \* Clips
- \* Cutting template 1: 1

Addition: Valve with overflow

Make sure all parts are in place before assembly commences.

When placing the sink in the worktop, space should

be used for bench mounting of the mixer between the wall and the wash basin.

Cut holes in worktop according to 1: 1 cutout template. Place the sink in the worktop and screw the fixing screws that are located in the clips along the side of the tub.

For maximum leg thickness 40mm.

## SPARE PARTS:

Klips: 1926001



# Maintenance VK44inset

## MAINTENANCE: INTRAS PRODUCTS IN STAINLESS STEEL

In order for your stainless steel AISI304 Intra product to retain original quality and appearance, we recommend regular cleaning. Use mild soap or detergents specially designed for stainless steel and clean water. Then wipe the surface with a dry cloth. Never use cleaners containing chlorine, iodine, fluorine or abrasives in stainless steel.

Also avoid contact with acid solutions and other substances that are not compatible with stainless steel.

Remember, for example, foods and skin care products can contain such substances, such as ketchup, juice, salt, some cleansing and nail polish, etc. Remove the spill immediately.

Take care of the following:

- \* Do not allow water or other liquid to dry. This is to avoid shielding on the surface.
- \* Even if stainless steel withstands hard handling, it will easily scratch sharp objects. For products with a normal polished (brushed) finish, this will look good when the product is new, but after a while it will be leveled out without the steel losing its shine. For satin and sanded products, the scratches will always be clearly visible. Never use scouring powder or steel wool in stainless steel. In addition to scratching the steel, steel wool leaves small particles that can develop into rust spots that can over time attack the steel.
- \* Stainless steel must not be in contact with or in chlorine solutions for a long time.
- \* Silverpuus puts spots that can not be removed.



Wondershare  
PDFelement

# Utility sink VK50inset

**Art. no.** VK50NF  
**GTIN** 7393069022216



<b>Overall dimension in mm</b>	555 x 455 x 230
<b>Depth in mm</b>	230
<b>Bowl dim. in mm</b>	500 x 400 x 230
<b>Cut-out dimension, inset model</b>	520 x 420, R80
<b>Waste hole dim. in mm</b>	Ø52
<b>Volume in L</b>	34
<b>Material</b>	AISI 304
<b>Material thickness in mm</b>	0,9
<b>Gross weight in kg</b>	4.00
<b>Weight, pallet</b>	96.00
<b>Pcs per pallet</b>	24

## Description

Utility sink in stainless steel, for inset. Supplied with fixing clips and hole for overflow.

## Installation

Cut a hole in the table top using the enclosed 1:1 template. Place the sink in the hole. Fasten the sink to the table top from underneath with the fixing clips.

# Installation VK50inset

## ASSEMBLY:

### Included in the box:

- \* Wash basin
- \* Clips
- \* Cutting template 1: 1

Addition: Valve with overflow

Make sure all parts are in place before assembly commences.

When placing the sink in the worktop, space should be used for bench mounting of the mixer between the wall and the wash basin.

Cut holes in worktop according to 1: 1 cutout template. Place the sink in the worktop and screw the fixing screws that are located in the clips along the side of the tub.

For maximum leg thickness 40mm.

## SPARE PARTS:

Klips: 1926001



# Maintenance VK50inset

## Maintenance of Intra products in stainless steel

Congratulations on your purchase of an Intra product that has been produced with care and to a high quality. Many of our products are supplied with a plastic film. This film protects the product during the transport and has to be removed before use.

To keep the original quality of your Intra product in AISI304 stainless steel, we recommend regular cleaning. Use washing up liquid and clean water to clean the product after use. Rinse carefully and dry.

Don't forget to clean all loose parts, e.g. the drain grating.

Please have the following in mind

- Don't let water or other liquids dry on the product. In this way you avoid that a grey coating builds up on the steel.
- Stainless steel can stand hard treatment but sharp objects can easily scratch the surface. These scratches are more visible when the product is new. After a period of use these

marks will be smoothed out, without the product losing its lustre.

- Never use scouring powder or steel wool to clean the surface. Apart from the risk of scratches, there is also a risk that rust stains will attack the steel.
- Avoid Chlorine based solutions coming into contact with the stainless steel.
- Silver polish leaves spots that cannot be removed.
- Food-stuffs that contain acid or other substances must quickly be removed (e.g. juices, salt, mustard, mayonnaise).

## Discoloration

More stubborn spots are often caused by impurities in the water or household substances. These can be removed with special polish agents for stainless steel.

We recommend the use of Intra Shining Kit. Dull spots can become lustrous again if rubbed with chalk on a soft cloth.

# Utility sink VK60inset

**Art. no.** VK60NF  
**GTIN** 7393069022407



<b>Overall dimension in mm</b>	660 x 510 x 250
<b>Depth in mm</b>	250
<b>Bowl dim. in mm</b>	600 x 450 x 250
<b>Cut-out dimension, inset model</b>	620 x 470, R80
<b>Waste hole dim. in mm</b>	Ø52
<b>Volume in L</b>	47
<b>Material</b>	AISI 304
<b>Material thickness in mm</b>	0,9
<b>Gross weight in kg</b>	4.80
<b>Weight, pallet</b>	101.80
<b>Pcs per pallet</b>	16

## Description

Utility sink in stainless steel, for inset. Supplied with fixing clips and hole for overflow.

## Installation

Cut a hole in the table top using the enclosed 1:1 template. Place the sink in the hole. Fasten the sink to the table top from underneath with the fixing clips.