

Basement drain DN 100, Black grating, 150 x 190 mm



Article information

Item no.: 33101 GTIN: 4026092007860 Discount group: 01

Advantages

- Integrated odour trap
- Including sludge bucket

Description

The basement drain made of polymer for floor slab installation is equipped with an odour trap and a sludge bucket. The upper section with slotted grating is vertically adjustable.

Version:

Odour trap:	included
Sealing water height:	50 mm
General characteristics:	
Nominal size (DN): Outer diameter (OD): Standard:	100 110 EN 1253-1
Dimensions:	
Length: Width: Cutout dimension, length: Cutout dimension, width:	285 mm 170 mm 320 mm 190 mm
Tank:	
Installation depth:	210 - 240 mm

Drain body:



Material of drain body: Socket version:

Vertical adjustment: Vertical adjustment:

Coverage features:

Type of cover: Cover material: Colour of cover: Load class: Length: Width: Sludge bucket: Locking: PP lateral

vertically adjustable upper section 25 - 55 mm

Slotted cover Polymer black K 3 (EN 1253-1) 150 mm 190 mm yes placed

Grating:

Rim length:	200 mm
Rim width:	159 mm
Rim material:	Polymer

Upper section material: Discharge rate (l/s) with 20 mm backwater: Polymer Polymer

1.8 l/s