


Geberit Mapress Carbon Steel bend adapter 90° with female thread



Example image



Application purposes

- For cooling and heating water without antifreeze agent
- For cooling and heating water with antifreeze agent
- For district heating water $\leq 120^\circ\text{C}$
- For extinguishing water (wet)
- For sprinklers (wet)
- For compressed air (oil purity class 3)
- For technical building systems, industry and shipbuilding

Characteristics

- Pressing indicator
- Leaky if unpressed
- Outside zinc-plated
- Seal ring made of CIIR, black
- Pressing socket with transparent protection plug

Technical data

Product material | Non-alloy steel 1.0034 E195 (EN 10305)

Art. no.	DN	d, \emptyset	Rp	arc	L	L1	Z	Z1
20552	12 / 10	15 mm	3/8 "	90°	4.9 cm	4.5 cm	2.9 cm	3.4 cm
20553	12 / 15	15 mm	1/2 "	90°	4.9 cm	4.8 cm	2.9 cm	3.3 cm
20555	15	18 mm	1/2 "	90°	5.3 cm	5.2 cm	3.3 cm	3.7 cm
20557	20	22 mm	3/4 "	90°	6.1 cm	6 cm	4 cm	4.4 cm
20558	25 / 15	28 mm	1/2 "	90°	7.2 cm	6.5 cm	4.9 cm	5 cm
20559	25	28 mm	1 "	90°	7.2 cm	6.6 cm	4.9 cm	4.7 cm
20560	32	35 mm	1 1/4 "	90°	6.8 cm	7.5 cm	4.2 cm	5.4 cm
20561	40	42 mm	1 1/2 "	90°	8 cm	8.4 cm	5 cm	6.3 cm
20562	50	54 mm	2 "	90°	10 cm	10.4 cm	6.5 cm	7.8 cm

Accessories

- Fastening for Geberit Mapress elbow adapter 90°