


Uponor S-Press PLUS tee reducer 25-16-20

1070573

- Made of tin-plated DR brass



About Uponor S-Press PLUS tee reducer

Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with inspection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:

- Male and female threads acc.to EN 10226-1.

Certification


- Approvals by local OM.

E.g.

- DVGW
- AENOR

Uponor S-Press PLUS tee reducer 25-16-20

1070573



Technical data

| | |
|----------------------------|-----------|
| Item no VVS | 045476325 |
| Item no NRF | 5114498 |
| Item (unit of measurement) | pce |
| Length (l1) | 44 mm |
| Length (l2) | 38 mm |
| Length (l3) | 38 mm |
| z2 | 19 mm |
| z3 | 17 mm |
| Packaging Quantity PL1 | 5 |
| Packaging Quantity PL3 | 40 |
| Packaging Quantity PL4 | 1920 |

Technical documents

[Download documents here](#)

Uponor UK

Blackmor Lane The Pavilion
WD18 8GA, Watford
UK

T +44 (0)1923 927000
E enquiries.uk@uponor.com

www.uponor.com/en-gb