


Uponor S-Press PLUS tap elbow M 25-Rp3/4"FT

1070642

- Made of tin-plated DR brass
- for on wall installation or attachment with rotation protection to the Uponor Smart Aqua mounting angles and plates.



Application information Uponor S-Press PLUS tap elbow M

Specification

- Unique press indicator
- Fast 3-step installation (press without bevel)
- Innovative QR code for immediate digital access
- Colour code
- Fixed press sleeve with inspection window
- Precise jaw fixation
- Fast diameter recognition
- Accurate test safety function
- 100% backward compatible with existing Uponor components
- Flow rate optimized fitting body

Application

- Tap water: The permanent operating temperature ranges from 0°C to 70°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 95°C for a period of 100 hours in the operating life time.
- Heating: The permanent operating temperature ranges up to 80°C at a maximum permanent operating pressure of 10 bar. The short-term malfunction temperature is 100°C for a period of 100 hours in the operating life time.

if not different mentioned:


- Male and female threads acc.to EN 10226-1.

Certification

- Approvals by local OM.
- E.g.
- DVGW
 - AENOR

Uponor S-Press PLUS tap elbow M 25-Rp3/4"FT

1070642



Technical data

Item no VVS	045475125
Item no NRF	5114552
Item (unit of measurement)	Piece
Female thread Rp	3/4 inch
Length (l1)	54 mm
Length (l2)	27 mm
Length (l3)	25 mm
Z-measurement k	40 mm
Z-measurement z3	8 mm
Packaging Quantity PL1	5
Packaging Quantity PL3	20
Packaging Quantity PL4	960

Documents

Page with all documents

Uponor Corporation

Ilmalantori 4
00240, Helsinki
Finland

T +358 (0)20 129 211
E info@uponor.com
F +358 (0)20 129 2841

www.uponor.com